

## JATAS Machinery Sales Inc.




503 Frontage Ave. W  
Underwood, MN 56586  
800-743-2435 / 218-826-6464



## Semi-Automatic Hydraulic Swivel Head Mitering

- ▢ Model Number : SH-650M
- ▢ Design Style : Single Side Swivel/Hinge Type

### Specifications

Angle		 0°	 +45°	 +60°
Max. Capacity	Round	420 mm (16.5")	400 mm (16")	250 mm (10")
	Rectangular(H x W)	380 x 650 mm (15" x 25.6")	400 x 400 mm (16" x 16")	400 x 250 mm (16" x 10")
Saw Blade	Speed	20-100 m/min (66-330 fpm)		
	Size (LxWxT)	5300L x 34W x 1.1Tmm (209" x 1.3" x 0.042")		
	Tension	Hydraulic		
Motor Output	Saw Blade	5 HP (3.75 KW)		
	Hydraulic	1 HP (0.75 KW)		
	Coolant pump	1/8 HP (0.09 KW)		
Tank Capacity	Hydraulic	45 L (11.7 gal)		
	Coolant	60 L (15.6 gal)		
Work Bed Height		750 mm (29.5")		
Net Weight		1200 kgs (2640 lbs)		
Gross Weight		1500 kgs (3300 lbs)		
Floor Space(LxWxH)		2300 x 2900 x 2500 mm (90.6" x 114" x 98.4")		
Shipping Space(LxWxH)		2920 x 2005 x 2110 mm (115" x 79" x 83")		

## **SH-650M Machine Features**

### **Structure**

- Swivel sawhead mitering from 90 to 60 degrees
- Rigid and heavy-duty pivot and trunion
- Sturdy cast work table
- 24.5" solid discharge table with coolant return

### **Blade Drive**

- Variable speeds from 80 fpm thru 350 fpm
- Infinitely variable blade speed (option)

### **Blade Guidance & Lubrication System**

- Carbide blade guides with roller bearings
- Two additional bearings to support blade from the top
- Cast iron guide arm supported by heavy-duty cast iron dovetail
- Automatic hydraulic blade tensioning device
- Integral coolant system
- Synchronized blade brush

### **Control & Automation**

- Precision feed pressure & feed rate dual valve system
- Conveniently designed control station
- Electrical components located inside the control box with main lockout disconnect
- Work height selector
- Industrial rated hydraulic components

### **Material Feeding & Clamping**

- 24.5" solid discharge table with coolant return
- 36" infeed roller table
- Full stroke machine vises

### **Safety**

- Breakage breakage detector
- Motor start interlock
- Orange alert safety design

### **Standard Accessories**

- Built-in adjustable material stop
- Adjustable work light
- Additional flushing hose
- Bi-metal saw blade
- Tool box, leveling pads, and an additional wire brush
- Operation & parts manual

Design and specifications are subject to change without notice and obligation.

Floor plan

